

## QB2-Plus

### Quick Break Tester & Shot Timer

The QB2-Plus provides a quantitative verification of Quick Break function and measures the duration of the magnetizing shot. The QB2-Plus can verify the correct function of AC, HWDC, and FWDC equipment, and verify Quick Break function on 3-phase FWDC units. Shot time and Quick Break voltage are alternately shown on the LCD display after each reading.



#### BENEFITS

- Simultaneous measurement of Shot Time and Quick Break
- Can be used with coils and cable wraps over 25 in (64 cm) diameter
- Quantitative results provide true verification of equipment

#### SPECIFICATIONS

For use with systems conforming to:

- ASTM E709
- ASTM E1444
- ISO 9934
- ASTM E3024

#### PART NUMBER

628989

**NOTE:** The QB2-Plus does not carry a CE mark and is not labelled to EU standards.

#### USE RECOMMENDATIONS

The QB2-Plus probe is placed inside the coil (or in line with a cable wrap) during a magnetizing shot. Quick Break voltage and Shot Time (in seconds) are alternately shown on the LCD display. A reference table of minimum Quick Break voltages for different coil diameters is included on the back of the meter.

#### PRODUCT PROPERTIES

<b>Shot Time Range</b>	
<b>1-phase mode</b>	0.40 to 5.00 seconds
<b>3-phase mode</b>	0.40 to 2.80 seconds
<b>Shot Time Accuracy</b>	+/- 0.02 seconds
<b>Quick Break (3-phase only)</b>	0 to 30 V +/- 0.2 V
<b>Display</b>	Dot-matrix LCD
<b>Power Supply</b>	DC 9V Battery
<b>EN/EC</b>	RoHS