
NDT Supply.com, Inc.

7952 Nieman Road Lenexa, KS 66214-1560 USA



NDT Supply 6 mm UV & White Light Videoscope





The UV Videoscope has both Visible - White Light and 365nm UV illumination making it an excellent inspection instrument. These scopes are available in 6mm diameter, and either 1 or 2 meter working lengths. They have 4-way articulation and Stainless-Steel Sheathing (Tungsten Sheathing is optional). The display is a 4.5" TFT LCD for clear, sharp images with 800 x 640 Resolution. USB Storage of still photos in 640x480 jpg format, and video recording at 640 x 480 avi format.



4-Way Articulation

Camera and Optical system

Carriera and Optical System		
Model No	6.0UV	
Diameter	6.0mm	
Rigid portion	15mm	
Housing	Steel Alloy	
Field of view	90°	
Direction of view	Forward	
Depth of view	10-50mm	
Illumination	4 White LEDS and UV Light Source	
Image sensor	1/10 inch color	
Effective pixels	450,000	
Photo recording	640 x 480Jpg	
Video	640 x 480Avi	
FPS	30	

Phone: 913-685-0675 Fax: 913-685-1125

NDT Supply.com, Inc. 7952 Nieman Road

Lenexa, KS 66214-1560 USA



NDT Supply 6 mm UV & White Light Videoscope

Display Unit

sioping out		
LCD Panel	4.5" 16:9 TFT LCD	
USB Connect	Micro USB	
Video Output	TV Out (NTSC/PAL)	
Recording Media	SDHC Card, support 32GB	
Photo	640 x 480 jpeg	
Video	640 x 480Avi	
Power source	Lithium battery 4200mAh	
	AC adapter: Input 100-240VAC 50/60Hz, Output 5VDC	

Operating Environment

Operating	Distal end and insertion tube: 0-80°C (for 3.9, 5.5 and 8mm camera)		
Temperatures	Other parts except for above: 0-40°C		
Operating Humidity	15-90% RH		
Waterproof	Insertion tube	IP58	
	Other parts	Not waterproof construction	



Phone: 913-685-0675 Fax: 913-685-1125