NDT Supply.com

7952 Nieman Road Lenexa, KS 66214 USA




Phoenix PX-45 Series Smart NDT LED UV Lamp with built-in HD Camera

Meets Rolls-Royce RRES 90061 Requirements
ASTM E1417, ASTM E1444, ASTM E709, ASTM E2297, ASTM E3022 compliant.



THE PERFECT SOLUTION FOR DOCUMENTING FLUORESCENT INDICATIONS



Close-up image of PSM-5
Panel Indication (PT)



Close-up image of MTU-3
Block Indication (MT)



MTU-3 Block Indication (MT)

ASTM Code Compliant UV Lamp

Features:

- 3 UV-A LEDs (365nm) and 1 White Light LED
- 4,500 μW/cm² UV-A @ 15" (38 cm) / less than 2 foot candles of white light
- 12.8 megapixel HD Camera for high resolution photos and videos of cracks and other fluorescent and visible indications.
- Meets ASTM UV-A intensity and wavelength specifications for FPI and MPI
- Touchscreen Zoom
- Data transmission via built-in WiFi, Bluetooth or Micro-USB connection
- 32GB Storage memory
- AC and Battery Operation with Battery Indicator
- IP67: Waterproof
- Phoenix Pro Version Only: Interchangeable Lens and Filters


Phone: 913-685-0675 sales@ndtsupply.com Fax: 913-685-1125 www.ndtsupply.com

NDT Supply.com

7952 Nieman Road Lenexa, KS 66214 USA



Uniform Beam even at close lamp to part distance



High Definition (HD) 12.8 Megapixel Camera



Data transmission via built-in Wi-Fi or Micro-USB connection



Phone: 913-685-0675 Fax: 913-685-1125

NDT Supply.com

7952 Nieman Road Lenexa, KS 66214 USA



Technical Specifications for Phoenix Series PX-45C and PX-45C Pro:

LEDs:	3 UV LEDs, 1 White Light LED
Intensity:	4,500 μW/cm ² @ 15" (38cm)
Visible Light:	< 2 Foot Candles (5 Lux)
Wavelength:	365 - 370 nm (365nm Peak)
Expected Lifespan:	30,000 hours
Coverage Area:	8" x 8" / 200 x 200 mm
Power Supply:	Battery and Mains Battery: 18650 Lithium battery (rechargeable) Mains: AC 110V-240V/ 50HZ / single phase
Weight:	1.9 lbs. (860g)
Cooling System:	Mechanical without fan
Battery:	18650 Lithium Battery (2) (rechargeable)
Function:	Camera + Video with playback support
Camera:	HD 12.8 Megapixels
Display Screen Size:	3 inches
White Balance:	Automatic white balance
Focus:	Auto focus system
Screen Resolution:	720p x 720p
Touchscreen:	Capacitive screen, Multi-touch
RAM:	8GB
Storage:	32GB SD Card
Data Transmission:	USB, WiFi, Bluetooth
Operating System:	Android 4.4
Others:	Email, Calculator, Time Display, Data Display, etc.
Compliance:	RRES 90061, ASTM E1417, ASTM E1444, ASTM E709, ASTM E2297, ASTM E3022, ISO9001

*Technical Specifications for Phoenix PX-45C Pro (only):

Interchangeable Lens and Filters: Meets demanding photographing needs. (All other specifications are the same.)

Phone: 913-685-0675 Fax: 913-685-1125

NDT Supply.com 7952 Nieman Road

Lenexa, KS 66214 USA





Phoenix PX-45C Standard and PX-45C Pro Lamp Kits Include:

- Phoenix Series LED UV Lamp
- AC Power Cable / Charger
- 18650 Lithium Batteries (qty. 4) (replaceable)
- UV Goggles
- Rugged Portable Carrying Case
- USB cord









Phone: 913-685-0675 Fax: 913-685-1125