SPECTROLINE® OPTIMAX[™] Multi-Lite[™] NDT Inspection Kit

(U.S. Patent No. 5,905,268; other patents pending)

A New Powerful, Versatile, Multi-LED, NDT Light Source!

The **OPK-300N Multi-Lite**[®] **Kit** features <u>three</u> Qwik-Connect[™] interchangeable LED lamp heads that connect to a rugged, blackanodized flashlight body. It provides single-wavelength illumination in UV-A and blue light, and is ideal for both pre-screening of fluorescent particles in ambient light conditions and fullfledged NDT inspections utilizing magnetic particles or fluorescent penetrants. A convenient white light LED provides general illumination of dark work areas.

Key Features:

- Super-powerful LED optical output with ultra-high intensity 365 nm UV-A and 450 nm blue light performance
- Provides nominal steady-state intensity of 18,000 μW/cm² (UV LED) or 7,000 μW/cm² (blue light LED) at 15 inches (38 cm)
- Blue light LED with patented thin-film dichroic lens filters out long-wave visible light
- Electronic Intensity Stabilizer ensures consistent performance. Beam strength will not weaken between charges!
- Instant-on operation. Lamp reaches full intensity immediately!
- · Lightweight, cordless, ergonomic design eliminates fatigue
- Meets ASTM UV-A intensity specifications for FPI and MPI
- Powered by a rechargeable NiMH battery. Provides 90 minutes of continuous inspection between charges (smart AC and DC chargers included). AC charger available in 120V, 230V, 240V and 100V versions.

The **OPK-300N Multi-Lite™ Inspection Kit** comes complete with three storage pouches for the LED lamp heads, smart AC and DC battery chargers, UV-absorbing spectacles, yellow contrasting spectacles and a padded carrying case.

ISO 9001:2008

CERTIFIED COMPANY

SPECTRONICS CORPORATION

NDT Supply.com, Inc. 7952 Nieman Road Lenexa, KS 66214-1560 USA Phone: 913-685-0675, Fax: 913-685-1125


e-mail: sales@ndtsupply.com, www.ndtsupply.com







OPTIMAX[™] *Multi-Lite[™]* NDT Inspection Kit


The OPK-300N features a compact, lightweight, corrosion-resistant aluminum flashlight body and three unique Qwik-Connect™ interchangeable LED lamp heads (UV-A, blue and white light). It is specially designed to provide the NDT professional with outstanding singlewavelength illumination for maximum versatility.








SURFACE CONTOUR PROFILE AT 15 IN (38 CM)



TOP INTENSITY PROFILE AT 15 IN (38 CM)



LAMP SPECIFICATIONS

Cordless flashlight body with three interchangeable LED lamp heads Style Length 9.0 inch (22.9 cm) Weight (with battery) 15.3 oz (434 g) **Power requirement** 3.6V, 2 AH NiMH internal battery stick (rechargeable) **Run time** 90 minutes (continuous) Charge time 5 hours Spectacles: UVS-30 UV-absorbing, clear CE UVS-40 yellow contrasting PECTRONICS NDT Supply.com, Inc. CORPORATION 7952 Nieman Road Lenexa, KS 66214-1560 USA

956 Brush Hollow Boad, P.O. Box 483 Westbury, New York 11590 800-274-8888 • 516-333-4840 Fax: 800-491-6868 • 516-333-4859 www.spectroline.com

Phone: 913-685-0675, Fax: 913-685-1125 e-mail: sales@ndtsupply.com, www.ndtsupply.com LY.COM